

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

MARKED UP VERSION

1

~~Description~~

~~Brush system for an electromotive drive unit~~

BRUSH SYSTEM FOR AN ELECTROMOTIVE DRIVE UNIT

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a U.S. national stage application of International Application No. PCT/EP2005/050238 filed January 20, 2005, which designates the United States of America, and claims priority to German application number DE 10 2004 006 557.8 filed February 10, 2004, the contents of which are hereby incorporated by reference in their entirety.

TECHNICAL FIELD

10 The invention relates to a brush system for an electromotive drive unit and to an electromotive drive provided with a brush system of this kind.

BACKGROUND

15 In electromotive drives, stepped speed control is implemented using a resistor circuit. During operation, electrical energy is converted into thermal energy by said resistor circuit. This thermal energy may have a negative effect on the electromotive drive in respect of its service
20 life. Overheating of the drive and increased drive component wear may occur. If the resistor circuit is disposed inside the

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

MARKED UP VERSION

2

motor, an air flow suitable for cooling cannot generally be guaranteed. This leads to an unwanted heat concentration in sections of the resistor circuit or in the drive as a whole, which may ultimately result in component failure.

5 To dissipate or remove the thermal energy produced, a known solution is to use cooling fins, large-area heatsinks or supplementary ventilation. Another known solution is to increase the service life by using more temperature-resistant, more durable and therefore more costly drive components.

10 DE 101 29 234 A1 discloses an electric drive unit comprising a gear housing, a motor housing, a separately implemented, watertight-sealed electronics housing, a brush holder and a signal receiver disposed on said brush holder. The brush holder is provided with plug contacts to which
15 electronics provided in the electronics housing are electrically connected. In addition, the brush holder is fixed to the motor housing at the transition between the motor housing and the gear housing. No references to any kind of cooling measures are to be found in DE 101 29 234 A1.

20 SUMMARY

The object of the invention is to demonstrate a way of effectively removing heat energy created in an electromotive drive.

25 This object ~~is~~ can be achieved by a brush system for an electromotive drive unit, comprising a base plate, brush

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

MARKED UP VERSION

3

system elements mounted on the base plate, conductors
provided on or in the base plate and at least one electrical
flat resistor enclosed in a resistor housing, said resistor
housing being made of a thermally conductive material and
5 provided with air passage openings.

The base plate may have an essentially discoidal shape
and has a cut-out in its central area for accommodating the
armature shaft with the commutator. The resistor housing can
be disposed in the same plane as the base plate and can be
10 inserted in another cut-out in the base plate. The resistor
housing can be essentially disk-segment-shaped. The resistor
housing may be connected to the base plate via snap-in
connections. The flat resistor contained in the resistor
housing may be connected via connecting lugs to the conductors
15 of the base plate. The air passage openings may be bore- or
slit-shaped perforations through the resistor housing. The
resistor housing can be made of a light metal. The resistor
housing may be provided with surface-enlarging extensions.
The surface-enlarging extensions can be beads or flanges.
20 The surface-enlarging extensions can be air flow deflecting
elements. A surface-enlarging extension may be provided for
contacting the resistor housing to the motor housing. The
flat resistor can be a resistor foil, a meander-shaped flat
resistor or a wire-shaped resistor. The resistor housing
25 can be implemented in a gas-, liquid- and particle-tight
manner. The resistor housing can be implemented in an open
manner. An electromotive drive may have such a brush system.

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

MARKED UP VERSION

4

~~using a brush system having the features set forth in Claim 1.~~
~~Advantageous embodiments and developments of the invention are~~
~~detailed in the dependent Claims 2 — 15. Claim 16 refers to an~~
~~electromotive drive having a brush system according to one of~~
5 ~~Claims 1 — 15.~~

The advantages of the invention are in particular that,
through the incorporation of the resistor unit in the brush
system and the special embodiment of the resistor unit as a
flat resistor contained in a resistor housing provided with
10 air passage openings, the air flow necessary for dissipating
the thermal energy produced can be better ensured than with
known drive systems. In addition, the flat implementation of
the resistor unit and its incorporation in the brush system
provides a compact, space saving design.

15 ~~The features specified Claim 2 mean that~~According to one
embodiment, the brush system can be slid over the motor shaft
and attached to the motor housing, thereby likewise ensuring a
space saving design as well as reliable contact-making of the
carbon brushes with the commutator segments of the electric
20 motor.

~~By means of the features set forth in Claims 3 and~~
~~4~~According to further embodiments, a space saving
disposition of the resistor unit in the brush system ~~is~~can
be achieved with optimum adaptation of the resistor unit to
25 the shape of the base plate of the brush system.

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

MARKED UP VERSION

5

~~The features detailed in Claim 5~~ According to another embodiment, ~~allow~~ the resistor unit can be allowed to be quickly and easily inserted in the brush system.

~~The connecting lugs specified in Claim 6~~ According to another embodiment, ~~the connecting lugs,~~ which are each preferably inserted in an associated receiving pocket of the resistor housing, may provide a simple means of contact between the resistor circuit contained in the resistor housing and an associated conductor on the base plate of the brush system.

According to ~~Claim 7~~ another embodiment, the air passage openings ~~are~~ can be holes or slits. These can advantageously be ready-made in the resistor housing during the resistor unit manufacturing process, care obviously having to be taken to ensure that the resistor circuit provided inside the resistor housing is not damaged.

If the resistor housing is made of aluminum, ~~as specified in Claim 8~~ according to another embodiment, or some other light metal, the entire brush system can be of lightweight construction.

~~By means of the features specified in Claims 9, 10 and 12~~ According to further embodiments, ~~there is~~ can be advantageously achieved an increase in the total surface area of the resistor housing available for heat dissipation.

The air flow deflecting elements ~~specified in Claim 11~~ according to another embodiment allow selective guidance of the air stream so as to enable heat to be effectively

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

MARKED UP VERSION

6

removed from strongly heat generating components and also to prevent removed heat from being conducted in the immediate direction of heat-sensitive components.

The resistor circuit contained in the resistor housing
5 can be a resistor film, a meander-shaped flat resistor or a resistor wire installed in a meandering manner.

The gas-, liquid- and particle-tight implementation of the resistor housing according to another embodiment
~~specified in Claim 14~~ has the advantage that the components
10 inside the housing are protected from corrosion and other damage caused by gases, liquids or particles present in the engine compartment.

An embodiment of the resistor housing ~~as claimed in Claim 16~~ allows an escape of gases, liquids or more precisely
15 moisture and particles which have penetrated the resistor housing in an undesirable manner during the production and use of the resistor unit.

BRIEF DESCRIPTION OF THE DRAWINGS

20 Further advantageous characteristics of the invention will emerge from their exemplary explanation with reference to the accompanying drawings in which:
Figure 1 shows a schematic view of the electromotive drive components essential for understanding the
25 invention,

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

MARKED UP VERSION

7

Figure 2 shows a more detailed schematic view of the brush system 6 of system 1,

Figure 3 shows a schematic rear view of the brush system 6 illustrated in Figure 2 and

5 Figure 4 shows a schematic view for explaining a development of the invention.

DETAILED DESCRIPTION

Figure 1 shows a schematic view of the electromotive
10 drive components essential for understanding the invention. An electromotive drive of this kind has a motor housing (not shown) in which permanent magnets 1 are disposed. The motor housing and the permanent magnets constitute a stator. In addition, the electromotive drive contains an armature 2 on
15 which coils 3 are provided. The armature 2 also comprises an armature shaft 4 on which a commutator with commutator segments 5 is mounted, said commutator segments being electrically connected to the windings of the coils 3.

The electromotive drive illustrated additionally has a
20 brush system 6 which, in the assembled state of the drive, is positioned around the shaft 4 in such a way that it is immediately adjacent to the commutator segments. When installed, this brush system 6 is fixed to the motor housing.

In addition, in the installed state of the drive, the
25 armature shaft 1 is mechanically coupled to a fan wheel 7 and drives same. The fan wheel 7 is so designed that, when it

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

MARKED UP VERSION

8

rotates with the shaft 4, air flows in the direction indicated by the arrow 8, i.e. essentially parallel to the shaft 4 of the electromotive drive.

By means of a special embodiment of the brush system 6, which will be explained in greater detail below with reference to Figures 2 - 4, it is ensured that at least part of the air flow produced by the fan wheel 7 effectively removes the heat energy generated from the motor.

Figure 2 shows a more detailed schematic view of the brush system 6 of Figure 1. The brush system 6 illustrated has a base plate 9 made of a non-electrically conductive material such as bakelized paper or plastic. The base plate 9 has an essentially discoidal, preferably circular discoidal basic shape and is provided with a cut-out 18 in its central area.

On the base plate 9 are mounted brush holder support elements 10 which are implemented e.g. as brush yokes. Inside these brush holder support elements 10 are mounted the carbon brushes which, in the operating state, make contact with the commutator segments 5. Also mounted on the base plate 9 are interference suppression elements such as chokes 11 and capacitors. On the base plate 9 there is additionally provided a mating connector 12 via which the brush system can be electrically contacted to an external voltage supply. The necessary electrical connections of the components mounted on the base plate 9 between one another and to other components are established via conductors 13 provided on the base plate. These conductors can be

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

MARKED UP VERSION

9

implemented in the form of a leadframe stamped from a metal sheet, as a circuit board or as individual conductor tracks either injected into the base plate or subsequently mounted on same. Hereinafter it will be assumed that the conductors
5 are implemented as conductor tracks.

According to the present invention there is incorporated in the brush system 6 a resistor unit having a resistor housing 14 and, provided in said resistor housing, a flat resistor arrangement hereinafter referred to as a
10 flat resistor. Said flat resistor is a resistor foil, a meander-shaped flat resistor or a resistor wire disposed in a meandering manner. This flat resistor is used as part of stepped speed control of the electromotive drive.

The resistor housing 14 has an essentially discoidal, preferably disk-segment-shaped basic form and consists of a
15 light metal, preferably aluminum. This allows the entire brush system to be of lightweight design.

As shown in Figures 2 and 3, the resistor housing 14 is an integral part of the brush system 6. The resistor housing
20 14 is disposed in the same plane as the base plate 9 and is inserted in a form-fit manner in another, preferably disk-segment-shaped cut-out in the base plate 9. The resistor housing 14 is attached to the base plate 9 by means of snap-in connections 17 into which the resistor housing is snapped
25 after its insertion. The resistor housing is inserted in the cut-out in the base plate from the underside of the base plate.

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

MARKED UP VERSION

10

The necessary electrical contacting of the terminals of the flat resistor disposed in the resistor housing 14 is effected using connecting lugs 16 which are pushed into the receiving pockets 20 of the resistor housing 14. The
5 connecting lugs 16 connect the terminals of the flat resistor to one of the conductor tracks 13 in each case. For example, one of the conductor tracks connects one terminal to an external power supply cable plugged into a contact of the connector 12 of the brush system 6. In addition, another
10 of the conductor tracks 13 connects the other terminal of the flat resistor to one of the carbon brushes via one of the interference suppression elements 11.

In order to be able to ensure good aeration and therefore good heat dissipation, the resistor housing 14 has
15 a plurality of air passage openings 15. These can be holes or slits ready-made in the housing during manufacture of the resistor unit 14. The more aeration is required, the larger the number of air passage openings can be. Alternatively or additionally, the size of the air passage openings can also
20 be varied.

Considering Figures 1 and 2 in conjunction, it is apparent that the air passage openings 15 are disposed in such a way that they allow the unrestricted passage of the air flow caused by the rotation of the fan wheel 7, thereby
25 effectively dissipating the heat generated by the resistor unit.

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

MARKED UP VERSION

11

Effective removal of the heat produced by the resistor unit is also assisted by the large-area, thermally conductive housing 14 which passes heat generated within the resistor housing to ambient.

5 In order to improve the heat dissipation still further, the resistor housing 14 is preferably provided with surface-enlarging extensions such as beads or flanges. In addition, these surface-enlarging extensions can also be air flow deflecting elements.

10 An example of an air flow deflecting element of this kind is illustrated in Figure 4. This is a sectional view showing one of the holes 15 and the parts of the resistor housing 14 above and below the hole. In addition, the arrows 8 indicate the air flow direction. It can be seen that the
15 air directed through the hole 15 in the resistor housing is diverted by the air flow deflecting element 19 and has a different flow direction on leaving the air flow deflecting element. By using air flow deflecting elements of this kind, the flow direction of the air can be influenced, making it
20 possible to direct more heat-dissipating air into areas containing components which generate a large amount heat.

 A surface-enlarging extension of the resistor housing 14 can also advantageously connect the resistor housing to the housing of the motor. Consequently, heat is also
25 dissipated via the motor housing, a measure which also counteracts overheating of the drive unit.

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

MARKED UP VERSION

12

According to one embodiment of the invention, the resistor housing can be made gas-, liquid- and particle-tight. This has the advantage of preventing gases, liquids or particles present, for example, in the engine compartment of a motor vehicle in which the drive unit is located from damaging the components contained in the housing during operation of the drive unit. In particular, this prevents corrosion from occurring.

According to another embodiment of the invention, the resistor housing can also be implemented in an open manner. This open design of the resistor housing has the advantage that gases, liquids or more precisely moisture and particles which get into the resistor housing during the production process and during operational use in an undesirable manner are also easily removed from it again.

The invention thus relates to a brush system which can be used in an electromotive drive. The brush system has a base plate, brush holder support elements mounted on said base plate and interference suppression elements. Additionally provided on the base plate are conductors via which the necessary electrical connections are established. The resistor unit containing a flat resistor disposed in a resistor housing is inserted in the base plate, fixed to same and placed in contact with the conductors. The resistor housing has air passage openings which facilitate an air flow caused by the rotation of a fan wheel. By means of this air flow, generated

~~PCT/EP2005/050238~~ /

ATTORNEY DOCKET NO.

PATENT APPLICATION

071308.0738

2003P17956WOUS

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

MARKED UP VERSION

13

heat, particularly heat produced during the operation of the flat resistor, is dissipated in an effective manner.

SUBSTITUTE SPECIFICATION
FOR NATIONAL PHASE SUBMISSION

MARKED UP VERSION

14

ABSTRACT

~~The invention relates to a~~ brush system for an electric
drive unit. ~~Said brush system comprises~~ has a base to which
brush system elements are fastened. Strip conductors via
5 which required electrical connections are established are
also provided on the base. Furthermore, a flat resistor that
is disposed in a resistor housing is inserted into the brush
system . ~~Said~~ The resistor housing is made of a thermally
conductive material while being provided with air passage
10 holes.